

Description:The USB omnidirectional microphone supports extremely wide frequency response, fast transient response and ultra-high sensitivity, and 360 degrees sound collection.

Specification:

| Model | TV-S63L |
|-------------------------------|---|
| Mic frequency response | 100Hz~22kHz |
| Speaker frequency response | 100Hz~22kHz |
| Speaker volume | 90dB |
| Pickup range | 4M radius, 360 degree full range |
| Port | USB port*1, LINE IN/OUT port*1 |
| Camera switch button | After the terminal joins the conference, switch to control the local/remote camera |
| Camera reset button | Camera reset to default position |
| Zoom in and zoom out button | Camera zoom in/out |
| Camera direction button | Control the direction of the camera, which are up, down, left, and right |
| Volume button | Volume down/up |
| Mute button | Speaker off/on |
| Microphone mute button | Microphone off/on |
| Video recording button | After the terminal joins the conference, start/stop conference recording |
| | (note: recording requires an external USB flash drive on the terminal) |
| Call button | Answer/Reject |
| Echo cancellation button | Press the video button, call button and volume up button at the same time to enter/exit the echo cancellation mode, |
| | enter the echo cancellation mode, the blue light flashes three times in the working state, |
| | and the blue light flashes twice in the working state when exit the echo cancellation mode. |
| Share content button | After the terminal joins the conference, start/stop sharing the content |
| Screen layout button | After the terminal joins the conference, switch the terminal screen layout |
| Button function | Support the control of the camera PTZ of the video conference terminal and zoom in and out; |
| | support the control of the recording of the video conference terminal; |
| | support the one-time buttoning of the video conference terminal; support the control of the video conference terminal menu; |
| AEC | > 65dB |
| AEC length | ≥500ms |
| Two-way noise compression(NC) | < 25dB |
| EMI | Support |
| AGC | Support |
| Power supply | USB Standard, 5V-1A |
| Dimension | 180*180*42mm |